DEMAND DATA SHEET

ROTARY POSITIVE DISPLACEMENT PUMPS

SIGMA PUMPY HRANICE

CUSTOMER

company/contact person: | VAT No:
address:
phone:
e-mail:

KIND OF OPERATION

continuous: ○ periodic: ○ intermittent: ○ part-loaded: ○ other: ○

PUMPED LIQUID

name: | density (kg/m^3):
temperature (°C): | impurities:
acidity pH: | viscosity (mm^2/s):

FLOW RATE

required Q (l/s):
range Q (l/min):

PRESSURE DIFFERENCE

required (bars):
range (bars):

PUMP SUCTION

in-flow (m):
suction lift (m):

REQUIRED MATERIAL VERSION OF THE PUMP

WORKING AMBIENT

basic: ☐ wet: ☐ damp: ☐ explosion hazard: ☐ other: ☐

ambient temperature (°C): | pump location:

PUMP DESIGN

horizontal: ○ gland packing: ○ other:
vertical: ○ mechanical seal: ○

DRIVE

yes: ○ no: ○

electric motor:

voltage: | protection IP:
frequency: | altitude above sea level:
starting Y/D: | zone:
ambient temperature: | explosion proof denomination Ex:

other:

frequency converter:

SCOPE OF DELIVERY

only pump: ○ with el.motor (common frame): ○ other scope: ○

OTHER REQUIREMENTS ON THE DELIVERY

SIGMA PUMPY HRANICE Ltd., Tovární č.p.605, 753 01 Hranice I-Město, phone: +420 581 661 267, fax: +420 581 661 785, e-mail: export@sigmapumpy.com

SAVE FORM | PRINT FORM | ! CLEAR FORM !